

储能电池系列

Energy Storage Battery Series



SUE2560

LFP Battery 2.56 kWh Stackable

磷酸铁锂电池 2.56kWh 堆叠式



Stackable installation
堆叠式安装设计



Built-in BMS management
内置BMS智能管理



IP21/IP65 optional
IP21/IP65可选



CAN/RS485 inverter protocol
支持主流逆变器协议



Master+Extension design
主电池(A)+扩展电池(B)组合



Grade-A cells, 8000 cycles
A级电芯, 循环寿命8000次

规格参数Specifications

型号Model	SUE2560
设计样式Case design	堆叠式 stackable
电池类型Battery Type	磷酸铁锂LiFePO4
电压 Normal Battery Voltage (Vdc)	51.2V
容量 Normal Capacity (25°C 0.2C)(Ah)	50Ah
能量 Normal Capacity (25°C 0.2C)(Ah)	2560WH
浮充电压 Float Charge Voltage (Vdc)	56.0V
电压范围 Operation Voltage range (Vdc)	40.0~58.4V
最大连续充电电流 (A) Max Continuous Charge Current (A)	25A
最大连续放电电流 (A) Max Continuous Discharge Current (A)	50A
最大脉冲放电电流 (A) Max Pulse Discharge Current (A)	75A 1Sec
端子 Terminal	M6
存储温度Storage temperature	0°C~30°C
防护等级IP degree	IP65
存储期限Storage duration	6月months at 25°C
安全标准Safety standard	UN38.3,MSDS
显示Display(可选Optional)	LCD
通讯Communication	CAN,RS485
保护Protection	
保护Protect	过充保护、过放保护、过流保护、短路保护、过温保护 Overcharge Protection, Over Discharge Protection, Over-Current Protection, Short Circuit Protection, Over Temperature Protection
环境Environment	
工作温度 Working Temperature	-10°C~+50°C
湿度Humidity	0~95%(no condensation)
最高海拔Sea Level(m)	≤1500
结构形状 Structural shape	
产品尺寸 Product Dimensions (mm)	460x360x139mm
包装尺寸 Packaging Dimensions (mm)	540x440x219mm
净重 Net Weight (kg)	23.2Kg
毛重 Gross Weight (kg)	25.0Kg